This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES


Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problems Mailbox.





(12) United States Patent

Karol et al.

(10) Patent No.: US 6,628,617 B1 (45) Date of Patent: Sep. 30, 2003

(54)	TRAFFIC ON CONNECTIONLESS AND CONNECTION-ORIENTED NETWORKS				
(75)	Inventors:	Mark John Karol, Fair Haven, NJ (US); Malathi Veeraraghavan, Atlantic Highlands, NJ (US)			
(73)	Accionee.	Lucent Technologies Inc. Murray Hill			

TECHNIQUE EOD INTERNETWORKING

(73) Assignee: Lucent Technologies Inc., Murray Hill,

NJ (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

	0.3.C. 134(b) by 0 days.
(21)	Appl. No.: 09/261,807
(22)	Filed: Mar. 3, 1999
(51)	Int. Cl. ⁷ H04L 12/56; H04L 12/64; H04L 12/66
(52)	U.S. Cl
(58)	Field of Search

(56) References Cited

U.S. PATENT DOCUMENTS

6,016,319 A	• 1/2000	Kshirsagar et al 370/399
6,055,561 A	 4/2000 	Feldman et al 370/220
6,091,725 A	* 7/2000	Cheriton et al 370/392
6,147,989 A	* 11/2000	Esaki et al 370/355
6,151,319 A	* 11/2000	Dommety et al 370/395.52
6,160,793 A	* 12/2000	Ghani et al 370/236

6,201,792	B 1	*	3/2001	Lahat 370/236
6,252,853	B 1	*	6/2001	Ohno 370/242
6,259,699	B 1	٠	7/2001	Opalka et al 370/389
6,317,431	B 1	•	11/2001	Hodgkinson et al 370/392
6,320,874	B1	+	11/2001	Crump et al 370/401
6,339,594	B1	•	1/2002	Civanlar et al 370/352
6,343,083	B1	•	1/2002	Mendelson et al 370/392
6,343,322	B2	*	1/2002	Nagami et al 370/395.3
6,343,326	B2	•	1/2002	Acharya et al 709/238
6,381,244	B 1	•	4/2002	Nishimura et al 370/395.21
6,490,252	B 1	٠	12/2002	Riggan et al 370/237


* cited by examiner

Primary Examiner—Hassan Kizou
Assistant Examiner—Ahmed Elallam
(74) Attorney, Agent, or Firm—Matthew J. Hodulik; Barry
H. Freedman

(57) ABSTRACT

Traffic on a connectionless (CL) network, such as IP packets, can be routed onto a connection a connection oriented (CO) network, such as an ATM telephony network, when it is advantageous to do so from a user or service provider viewpoint, without affecting the ability of users to continue to use existing applications. Routing is controlled by nodes called CL-CO gateways, with connectivity to both the CL network and the Co network. When CL traffic originating at a source reached these gateway nodes, a decision is made whether to continue carrying the information in the CL mode, or to redirect the traffic to a CO network. In accordance with one embodiment of the present invention, each CL-Co gateway includes hardware and software modules that typically comprise (a) interfaces to the Co network, (b) interfaces to the CL network (c) a moderately sized packet buffer for temporarily storing packets waiting for CO network setup or turnaround; (d) a database for storing forwarding, flow control header translation and other information, and (e) a processor containing logic for controlling the gateway packet handling operations.

19 Claims, 9 Drawing Sheets





US006597686B1

(12) United States Patent Smyk

(10) Patent No.:

US 6,597,686 B1

(45) Date of Patent:

*Jul. 22, 2003

(54) APPARATUS AND METHOD FOR INTERNET TELEPHONY ROUTING

- (75) Inventor: Darek A. Smyk, Piscataway, NJ (US)
- (73) Assignee: Telcordia Technologies, Inc., Morristown, NJ (US)
- (*) Notice:

This patent issued on a continued prosecution application filed under 37 CFR 1.53(d), and is subject to the twenty year patent term provisions of 35 U.S.C. 154(a)(2).

Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

- (21) Appl. No.: 09/063,684
- (22) Filed: Apr. 21, 1998

Related U.S. Application Data

(60) Provisional application No. 60/044,143, filed on Apr. 22, 1997.

(51)	Int. Cl. ⁷	·	H04L 12/66
(52)	U.S. Cl.	370/352: 370/4	01: 370/252

(56) References Cited

U.S. PATENT DOCUMENTS

4,771,425 A	9/1988	Baran et al 370/85
5,095,480 A	3/1992	Fenner 370/94.1
5,712,907 A	1/1998	Wegner et al 379/112
5,724,412 A	3/1998	Srinivasan 379/93.23
5,751,706 A	5/1998	Land et al 370/352
6,064,653 A •	5/2000	Farris 370/237

6.069.890	Α	٠	5/2000	White et al	370/352
				Smyk	
				Jonas et al	
				Farris et al	
				Chinni et al	

FOREIGN PATENT DOCUMENTS

JP

10-178503 6/1998

OTHER PUBLICATIONS

Yang, C., INETPhone: Telephone Services and Servers on Internet, RFC 1789, Apr. 1995, pp. 1-6.

* cited by examiner


Primary Examiner—Hassan Kizou Assistant Examiner—John Pezzlo

(74) Attorney, Agent, or Firm—Joseph Giordano; James W. Falk

(57) ABSTRACT

An apparatus and method for automatically designating a telephone call route through a telephone network including a circuit switched telephone network (STN) and a packet switched network, such as the Internet. The method includes the steps, executed by a network element, of receiving a telephone number corresponding to a called party receiving the telephone call, reviewing preference information pertaining to a calling party's telephone service, determining from the preference information and the telephone number whether the telephone call can be routed to the called party through the packet switched network, and assigning a route for the telephone call through one of either the packet switched network or the STN to the called party based on whether the call is routable through the packet switched network. A network element (NE) includes the databases and call processing records necessary to route a call and perform these steps.

6 Claims, 9 Drawing Sheets





US006584094B2

(12) United States Patent

Maroulis et al.

(10) Patent No.:

US 6,584,094 B2

(45) Date of Patent:

*Jun. 24, 2003

(54) TECHNIQUES FOR PROVIDING TELEPHONIC COMMUNICATIONS OVER THE INTERNET

(75) Inventors: Serafim Maroulis, Belford, NJ (US);
Mahendra Pratap, Cliffwood Beach,
NJ (US); Dennis W. Specht, Sparta, NJ

(73) Assignee: Avaya Technology Corp., Basking Ridge, NJ (US)

(*) Notice: This patent issued on a continued prosecution application filed under 37 CFR 1.53(d), and is subject to the twenty year patent term provisions of 35 U.S.C. 154(a)(2).

Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: 08/713,050

(22) Filed: Sep. 12, 1996

(65) Prior Publication Data US 2003/0081590 A1 May 1, 2003

(51) Int. Cl.⁷ H04L 12/66

(52) U.S. Cl. 370/352; 370/522; 379/900

(58)	Field of Search 370/400, 401,
	370/410, 522, 524, 230, 389, 352, 356,
	355: 379 <i>/</i> 229 <u>-</u> 232, 900

(56) References Cited

U.S. PATENT DOCUMENTS

5,604,737 A	٠	2/1997	Iwami et al	370/352
			Gordon	
5,790,548 A	•	8/1998	Sistanizadeh	370/401
6,078,579 A				
6,324,280 B2	*	11/2001	Dunn et al	370/352


* cited by examiner

Primary Examiner-Steven Nguyen

(57) ABSTRACT

Improved methods for providing a voice communications path over the internet. According to a first embodiment, a first PBX coupled to a first internet gateway device determines whether or not a second PBX has access to a second internet gateway device and, if so, the second PBX sends the IP (internet protocol) address of the second internet gateway device to the first PBX, and the first PBX sends the IP address of the first internet gateway device to the second PBX, over the PSTN (public switched telephone network) and/or over a network signalling channel. The first and second internet gateway devices then set up a voice communications path over the internet between the first and second PBXes.

15 Claims, 3 Drawing Sheets





(12) United States Patent Christie, IV

(10) Patent No.: US 6,445,695 B1 (45) Date of Patent: Sep. 3, 2002

(54)	SYSTEM AND METHOD FOR SUPPORTING
. ,	COMMUNICATIONS SERVICES ON BEHALF
	OF A COMMUNICATIONS DEVICE WHICH
	CANNOT PROVIDE THOSE SERVICES
	ITSELF

- (75) Inventor: Samuel H. Christie, IV, Cary, NC (US)
- (73) Assignee: Nortel Networks Limited, St. Laurent
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(56) References Cited

U.S. PATENT DOCUMENTS

6,031,896 A * 2/2000 Gardell et al. 370/352

Field of Search 370/264, 351-4,

370/389, 395.1, 395.61, 395.5, 419, 463,

465-469, 400-2

6,229,804	B1 *	5/2001	Lee et al
6,275,574	B1 *	8/2001	Naudus 370/352 Oran 370/352 Strathmeyer et al. 370/356
2001/0028649	A1 *	10/2001	Pogossiants et al 370/389 Anjum et al 370/401
			Kikinis 370/352

^{*} cited by examiner


Primary Examiner-David Vincent

(74) Attorney, Agent, or Firm—Withrow & Terranova, P.L.L.C.

(57) ABSTRACT

A system and method for supporting communications services on behalf of a communications device which cannot provide those services itself in a communications network based on functional signaling. A terminal is designed to identify a supporting server/terminal proxy upon initialization. Henceforth, the terminal provides each user input stimulus to the server and responds to stimulus from the server. The server manages the state machine of the terminal, provides supplementary services, and meets protocol requirements for the network interface.

16 Claims, 2 Drawing Sheets





(12) United States Patent

Voit et al.

(10) Patent No.:

US 6,295,292 B1

(45) Date of Patent:

Sep. 25, 2001

INBOUND GATEWAY AUTHORIZATION PROCESSING FOR INTER-CARRIER INTERNET TELEPHONY

(75) Inventors: Eric A. Volt, Baltimore; Edward E. Balkovich, Potomac, both of MD (US); Robert D. Farris, Sterling, VA (US); William D. Goodman, Collegeville, PA (US); Javant G. Gadre, Oakton; Patrick E. White, Vienna, both of VA (US); David E. Young, Silver Spring, MD (US)

Assignce: Bell Atlantic Network Services, Inc., Arlington, VA (US)

(*) Notice:

Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: 08/998,274

(22) Filed:

Dec. 24, 1997

Related U.S. Application Data

Continuation-in-part of application No. 08/931,159, filed on Sep. 16, 1997, now Pat. No. 6,137,869, and a continuation-in-part of application No. 08/931,480, filed on Sep. 16, 1997, and a continuation-in-part of application No. 08/931, 268, filed on Scp. 16, 1997, now Pat. No. 6,157,636, and a continuation-in-part of application No. 08/931,477, filed on Sep. 16, 1997, now Pat. No. 6,157,648, and a continuation-in-part of application No. 08/931,267, filed on Sep. 16, 1997, and a continuation-in-part of application No. 08/812, 075, filed on Mar. 6, 1997, now Pat. No. 6,104,711.

12/64
_

(52)

Field of Search 370/352, 353, 370/354, 355, 356, 400, 401, 402, 462,

(56)

References Cited

U.S. PATENT DOCUMENTS

5,247,571 9/1993 Kay et al. 379/207 5,608,786 3/1997 Gordon 370/352

(List continued on next page.)

OTHER PUBLICATIONS

Yang, C. "INETPhone: Telephone Services and Servers on the Internet," http://ds.internic.net/rfc/rfc1789.txt (Feb. 12, 1997).

Primary Examiner—Min Jung (74) Attorney, Agent, or Firm-McDermott, Will & Emery

ABSTRACT (57)

A communication system providing telephony communication across combined circuit switched and packet switched networks, such as a telephone network and the Internet, which are connectable to terminals, such as telephones and computers, for selective communication therebetween. The communication system provides an architecture and methodology for implementing initiation of establishment of a communication path between called and called terminals from a telephone terminal. The architecture and methodology facilitates communication across carriers or service providers, settlements between carriers and service providers, usage accounting across carriers and service providers, and usage allocation among carriers or service providers. Upon a terminal requesting connection to a gateway to establish a communication path between that terminal and a designated destination terminal, there occurs within the circuit switched network and a gateway to the packet network a transfer of an information package which identifies the calling station, the called station, and the identity of the responsible origination carrier or service provider. An authentication database of this carrier is accessed and authorization of the requested communication is secured. The second carrier or service provider is requested to complete the communication path. The second carrier or service provider consults a database of carriers or service providers, determines whether to authorize the communication, and upon arriving at an affirmative conclusion establishes the communication path, completes the communication, and compiles a charge to the first service provider and a statement of usage and presents the same to the first service provider.

46 Claims, 31 Drawing Sheets

